



# AGD420:- SINGLE GLASS DOOR SERIES



Pictured with additional row of shelves

## **AGD420**

### **FEATURES:**

- Operating Temperature 0° to +5° C @ ambient temperature of 40° C
- Only requires one standard power point (GPO):- 240V 50Hz 10 amp.
- Digital Temperature Display.
- Individual adjustable shelves per door maximizing display configurations.
- Individual light switch to interior and signage.
- Double glazed thermal insulated doors to reduce power consumption.
- Aluminium Framed doors with locks.
- Positive seal torsion bar self closing doors for low maintenance.
- Commercial castors, for ease of cabinet movement.
- Cyclic defrost with timed backup insures frost free refrigeration.
- Auto hot gas condensate removal requires no pumping.

## **MAIN DATA**

Specifications are subject to change without notice. E&OE.

Model	Doors	Volume (Net lts)	Shelves	Dimensions (mm) Width x Depth x height	Voltage	Power	Cord Length	Shipping Weight
AGD420	1	412	4	680 x 720 x 2045	240v/50hz	3 amp	2.4	138kg

Head Office: Unit 1/35 Rimfire Drive ,Hallam, Vic 3803. Phone: 1800 813 987 Fax: 03 8786 3572 Email: sales@austwiderentals.com websites: www.austwidesales.com.au or austwiderentals.com





# AGD420:- SINGLE GLASS DOOR SERIES

### **Specification**

- Shelves: 4 height adjustable, PVC coated, shelves per door. 4 stainless steel shelf clips per shelf fit to stainless steel shelf posts.
- Lighting: Florescent 36watt 1200mm tubes recessed into the inner walls provide high visibility lighting, with low replacement cost.
- Refrigeration System: Fully balanced self contained condensing unit with forced draught evaporator and condenser.
- Compressor. SECOP, formerly Danfoss compressors.
- Refrigerant: R134A.
- Defrost: Cyclic defrost, with nocost, hot gas condensate disposal. Supplemented with timed defrosts via electronic controller.
- Electronic Controller: Italian designed and Manufactured, Dixell temperature controller.
- Evaporator: Epoxy coated to minimize the potential of corrosion and thus future gas leaks.
- **Operation conditions:** 0° to 5° C. at up to 40° C ambient.
- **Electrical:** Units come ready for connection to 240volt 50hz 10amp GPO. It is recommended that a ded-

icated GPO be used.

- Construction: Corrosion resistant Pre-painted steel interior and exteri-
- Insulation: 50mm high density polyurethane foamed in place, Blowing agent, Cyclopentane for CFC free Ozone protection and superior insulating properties.
- Door: Double glazed thermal insulated toughened glass. Constructed with aluminium frame and fitted with locks.
- **Hinging:** Self closing torsion spring.
- Gasket: PVC welded one piece magnetic gasket. Removable without the need for tools.
- Castors: 4 (2 x locking) x 75mm swivel commercial castors.
- Model Features: Digital Temperature readout.

Warranty1: Austwide's Manufacturers warranty 12 month parts and labour. See terms and conditions of sale for full description.

#### **Optional Extras:**

- · Additional Shelves.
- Livery to sides and illuminated sian.

#### **Outstanding Benefits**

Condensing unit: Bottom mounted

- placing the unit in the coolest position, close to the floor, which puts less strain on the refrigeration system providing longer life and greater efficiency.
- Optimal product placement: The G420 lifts the product off the floor. placing it in the optimal position for your customers to easily reach in and retrieve without the need to stoop down excessively.
- AGD Series also available in a two Door: AGD920 pictured. There is also a matching Freezer Series AFD Series.





AGD920 shown with additional row of

Dims (mm): 1370w x 720d x2090h

ELEVATIONS. (not to scale)

1.terms and conditions apply. Visit web site for full details. www.austwidesales.com.au pecifications are subject to change without notice. E&OE.





Head Office: Unit 1/35 Rimfire Drive ,Hallam, Vic 3803. Phone: 1800 813 987 Fax: 03 8786 3572 Email: sales@austwiderentals.com websites: www.austwidesales.com.au or austwiderentals.com